Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

May 1998

National Semiconductor

DS14C89A
Quad CMOS Receiver

General Description

The DS14C89A, pin-for-pin compatible to the DS1489A/MC1489A, ia a quad receiver designed to interface data terminal equipment (DTE) with data circuit-terminating equipment (DCE). These devices translate levels conforming to EIA-232E and CCITT V.28 standards to TTL/CMOS logic levels.

The device is fabricated in low threshold CMOS metal gate technology. The device provides very low power consumption compared to their bipolar equivalents: 900 µA (DS14C89A) versus 26 mA (DS1489A).

The DS14C89A provides on chip noise filtering which eliminates the need for external response control filter capacitors.

When replacing the DS1489A with the DS14C89A, the response control filter pins can be tied high, low, or not connected.

Features

- Meets EIA/TIA-232-E and CCITT V.28 Standards
- Failsafe - Output High for Open Input
- LOW Power consumption
- On chip noise filter
- Available in SOIC Package

Connection Diagram



Order Number DS14C89AN, DS14C89AM,
See NS Package Number M14A, N14A

© 1998 National Semiconductor Corporation

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

V_{CC}	+6V
Input Voltage	−30V to +30V
Receiver Output Voltage	(V_{CC}) +0.3V to GND−0.3V
Junction Temperature	+150˚C
Continuous Power Dissipation @ +25˚C (Note 2)	
N Package	1513 mW
M Package	1063 mW
Lead Temp.	
(Soldering 4 seconds)	+260˚C
Storage Temp. Range	−65˚C to +150˚C
ESD Rating ≥ 1.8 kV, Typically ≥ 2 kV	
(HMB, 1.5 kΩ, 100 pF)	

Recommended Operating Conditions

	Min	Max	Units
V_{CC} (GND = 0V)	+4.5	+5.5	V
Operating Free Air Temp. (T_A)			
DS14C89A	0	+75	˚C

Electrical Characteristics

Over recommended operating conditions, unless otherwise specified

Symbol	Parameter	Conditions		Min	Typ	Max	Units
V_{TH}	Input High Threshold			1.3		2.7	V
V_{TL}	Input Low Threshold			0.5		1.9	V
V_{HY}	Typical Input Hysteresis				1.0		V
I_{IN}	Input Current	V_{IN} = +25V	V_{CC} = +4.5V to +5.5V	3.6		8.3	mA
		V_{IN} = −25V		−3.6		−8.3	mA
		V_{IN} = +3V		0.43		1.0	mA
		V_{IN} = −3V		−0.43		−1.0	mA
		V_{IN} = +15V	V_{CC} = 0V (Power-Off)	2.14		5.0	mA
		V_{IN} = −15V	(Note 4)	−2.14		−5.0	mA
		V_{IN} = +3V		0.43		1.0	mA
		V_{IN} = −3V		−0.43		−1.0	mA
V_{OH}	Output High Voltage	V_{IN} = V_{TL} (min)	I_{OUT} = −3.2 mA	2.8	4.0		V
			I_{OUT} = −20µA	3.5	4.7		V
V_{OL}	Output Low Voltage	V_{IN} = V_{TH} (max) I_{OUT} = +3.2 mA			0.15	0.4	V
I_{CC}	Supply Current	No Load, V_{IN} = 2.7V or 0.5V			0.5	900	µA

AC Electrical Characteristics (Note 3)

Over recommended operating conditions, unless otherwise specified, C_l = 50 pF

Symbol	Parameter	Conditlons	Min	Typ	Max	Units
t_{PLH}	Propagation Delay Low to High	Input Pulse Width ≥ 10 µs		3.5	6.5	µs
t_{PHL}	Propagation Delay High to Low	Input Pulse Width ≥ 10 µs		3.2	6.5	µs
t_{SK}	Typical Propagation Delay Skew			400		ns
t_r	Output Rise TIme			40	300	ns
t_f	Output Fall Time			40	300	ns
t_{nw}	Pulse Width assumed to be Noise				1.0	µs

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The tables of "Electrical Characteristics" specify conditions for device operation.

Note 2: Derate N Package 12.1 mW/˚C, and M Package 8.5 mW/˚C above +25˚C.

Note 3: AC input waveforms for test purposes: t_r = t_f = 200 ns, V_{IH} = +3V, V_L = −3V, f = 20 KHz.

Note 4: Under the power-off supply conditions it is assumed that the power supply potential drops to zero (0V) and is replaced by a low impedance or short circuit to ground.

Parameter Measurement Information



FIGURE 1. Receiver Load Circuit



FIGURE 2. Receiver Switching Waveform (Note 3)

Typical Application Information



FIGURE 3. Receiver Block Diagram



FIGURE 4. EIA-232D Data Transmission



Physical Dimensions inches (millimeters) unless otherwise noted



Order Number DS14C89AM
NS Package Number M14A



Order Number DS14C89AN
NS Package Number N14A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com

www.national.com

National Semiconductor Europe
Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 1 80-530 85 85
English Tel: +49 (0) 1 80-532 78 32
Français Tel: +49 (0) 1 80-532 93 58
Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group
Tel: 65-2544466
Fax: 65-2504466
Email: sea.support@nsc.com

National Semiconductor Japan Ltd.
Tel: 81-3-5620-6175
Fax: 81-3-5620-6179

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.